



Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: K2 VENTO OCEAN
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Air freshener
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Melle Sp. z o. o.

Stary Staw 9

63-400 OSTRÓW WLKP.

POLAND

· Further information obtainable from:

Product safety department. zakupy@inter-global.com.pl

• 1.4 Emergency telephone number: During normal opening times: 0048/62 737 88 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

1-(1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetrametyl-2-naphthyl)ethan-1-one 4-tert-butylcyclohexyl acetate

(Contd. on page 2)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 1)

(*Z*)-3,4,5,6,6-pentamethylhept-3-en-2-one

4-(4-hydroxy-4-methylpentyl)cyklohex-<math>3-enecarbaldehyde

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container to a waste container.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture: consisting of the following components.

Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-XXXX	ethanol ◆ Flam. Liq. 2, H225; ◆ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C≥50 %	<30%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<30%
CAS: 54464-57-2 EINECS: 259-174-3 Reg.nr.: 01-2119489989-04-XXXX	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ♣ Aquatic Chronic 1, H410; ♠ Skin Irrit. 2, H315; Skin Sens. 1, H317	<25%
CAS: 18479-58-8 EINECS: 242-362-4 Reg.nr.: 01-2119457274-37-XXXX	2,6-dimethyloct-7-en-2-ol Skin Irrit. 2, H315; Eye Irrit. 2, H319	<15%
CAS: 32210-23-4 EINECS: 250-954-9 Reg.nr.: 01-2119976286-24-XXXX	4-tert-butylcyclohexyl acetate Skin Sens. 1, H317	<5%
CAS: 67634-00-8 EINECS: 266-803-5	allyl (3-methylbutoxy)acetate Acute Tox. 4, H302; Skin Irrit. 2, H315	<5%
CAS: 81786-73-4 EINECS: 279-822-9	(Z)-3,4,5,6,6-pentamethylhept-3-en-2-one Aquatic Chronic 2, H411;	<5%
CAS: 31906-04-4 EINECS: 250-863-4 Reg.nr.: 01-2119489989-04-XXXX	4-(4-hydroxy-4-methylpentyl)cyklohex-3-enecarbaldehyde Skin Sens. IA, H317	<1%
CAS: 101-86-0 EINECS: 202-983-3 Reg.nr.: 01-2119533092-50-XXXX	α-hexylcinnamaldehyde Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ♦ Skin Sens. 1, H317	<1%

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

	(Contd.	
CAS: 52475-86-2	1-Methyl-4-(4-methyl-3-pentenyl)cyclohex-3-ene-1-	<19
EINECS: 257-942-2	carbaldehyde	
	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 4180-23-8	(E)-anethole	<19
EINECS: 224-052-0	(1) Skin Sens. 1, H317	
Reg.nr.: 01-2119979097-22-XXXX		
CAS: 81782-77-6	4-Methyl-3-decen-5-ol	<19
EINECS: 207-431-5	💠 Aquatic Acute 1, H400	
CAS: 101-84-8	diphenyl ether	<19
EINECS: 202-981-2	🕸 Aquatic Acute 1, H400; Aquatic Chronic 3, H412	
CAS: 91-64-5	Coumarin	<19
EINECS: 202-086-7	♦ STOT RE 2, H373; ♦ Acute Tox. 4, H302; Skin Sens. 1,	
Reg.nr.: 01-2119949300-45-XXXX		
CAS: 141-13-9	2,6,10-Trimethyl-9-undecenal	<19
	🔖 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🕠 Skin Sens. 1, H317	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Take affected persons out into the fresh air.

Personal protection for the First Aider.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 3)

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients	with limi	t values the	nt ronniro	monitoring	at the	worknlace.

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

101-84-8 diphenyl ether

WEL Short-term value: 14 mg/m³, 2 ppm Long-term value: 7 mg/m³, 1 ppm

· DNELs

64-17-5 ethanol

Oral	consumers-long-term systemic exposure	87 mg/kg m.c. (consumers)
Dermal	consumer-long-term systemic effect	206 mg/kg m.c (consumers)
	workers-long-term systemic exposure	343 mg/kg m.c. (workers)
	workers-short-term systemic exposure	1,900 mg/kg m.c. (workers)
Inhalative	consumer- long-term systemic effects	114 mg/m3 (consumers)
	workers-long-term exposure inhalation	950 mg/kg/m.c. (workers)

(Contd. on page 5)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

		(Contd. of page
· PNE	Cs	
64-17	7-5 ethanol	
Oral	microorganisms during wastewater treatment	580 mg/l (environment)
	soil	0.63 mg/kg (environment)
	sediment	3.6 mg/kg (environment)
	marine environment	0.79 mg/l (environment)
	freshwater environment	0.96 mg/l (environment)
	STP	2.75 mg/l (environment)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 5)

SECTION	9. Physical	and chemical	properties
BECHON	J. I mysicui	una chemicai	properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Light green
Characteristic
Not determined.

Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.

· Auto-ignition temperature: Product is not selfigniting.

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

water: Soluble.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

Density and/or relative density

Density:
Relative density
Vapour density
Not determined.
Not determined.
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

· Important information on protection of health and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

(Contd. on page 7)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 6)

· Substances and mixtures, which emit fl	lammable
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	25,000 mg/kg
64-17-5 et	hanol	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	>19,000 mg/kg (rab)
32210-23-	4 4-tert-bu	tylcyclohexyl acetate
Oral	LD50	5,000 mg/kg (rat)
67634-00-	8 allyl (3-n	nethylbutoxy)acetate
Oral	LD50	500 mg/kg (ATE)
101-84-8 diphenyl ether		
Oral	LD50	3,370 mg/kg (rat)
91-64-5 C	oumarin	
Oral	LD50	293 mg/kg (rat)
Skin corro	sion/irrita	tion Causes skin irritation.

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 8)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 7)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability The product is biodegradable. Degree of biodegradation> 70%
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1993
ADK, IMDU, IATA	UN1995
· 14.2 UN proper shipping name	
$\cdot ADR$	1993 FLAMMABLE LIQUID, N.O.S. (ETHANO)
	(ETHYL ALCOHOL)), ENVIRONMENTALL
	HAZARDOUS
\cdot $IMDG$	FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHY
	ALCOHOL), 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8
	tetramethyl-2-naphthalenyl)ethanone), MARIN
	POLLUTANT
·IATA	FLAMMABLE LIQUID, N.O.S. (ETHANOL)

age 9)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG	
Class Label	3 Flammable liquids. 3
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substance (Z)-3,4,5,6,6-pentamethylhept-3-en-2-one
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids.
EMS Number:	F-E,S-E
Stowage Category	\overline{A}
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L Code: El
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANC (ETHYL ALCOHOL)), 3, III, ENVIRONMENTALI HAZARDOUS

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 9)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- 2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Local regulations.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)

Printing date 11.05.2021 Version number 4 (replaces version 3) Revision: 11.05.2021

Trade name: K2 VENTO OCEAN

(Contd. of page 10)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3