

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Page 1/9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: K2 TIRE DOKTOR

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Tire Inflator
- \cdot 1.3 Details of the supplier of the safety data sheet

• *Manufacturer/Supplier: Melle Sp. z o. o. Stary Staw 9* 63-400 OSTRÓW WLKP. POLAND

 Further information obtainable from: Product safety department. zakupy@inter-global.com.pl
1.4 Emergency telephone number: During normal opening times: 0048/62 737 88 00

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- *The product is classified and labelled according to the CLP regulation. Hazard pictograms*



· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · Precautionary statements
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- *P271* Use only outdoors or in a well-ventilated area.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- *P501* Dispose of contents/container to a waste container.

(Contd. on page 2)

GB

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

(Contd. of page 1)

• 2.3 Other hazards • Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· Description: Mixture: consisting of the following components.

Dangerous components:				
CAS: 74-98-6 EINECS: 200-827-9	propane	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<15%	
CAS: 75-28-5	isobutane	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<15%	
EINECS: 200-857-2 CAS: 106-97-8	butane, pure		<15%	
EINECS: 203-448-7	-			
• Additional information: For the wording of the listed hazard phrases refer to section 16				

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information:

Take affected persons out into the fresh air.

Personal protection for the First Aider.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Generally the product does not irritate the skin.*
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

- *Use fire extinguishing methods suitable to surrounding conditions.*
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

^{· 3.2} Mixtures

Version number 3 (replaces version 2) Revision: 17.03.2022 Printing date 17.03.2022 Trade name: K2 TIRE DOKTOR (Contd. of page 2) · 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. · Information about fire - and explosion protection: Protect from heat. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. • 7.2 Conditions for safe storage, including any incompatibilities · Storage: • Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Store away from oxidising agents. • Further information about storage conditions: Store in a cool place. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. • 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

GB

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

(Contd. of page 3)

· Individual protection measures, such as personal protective equipment

• General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

· Respiratory protection: Not required.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical p	properties	
General Information		
Physical state	Aerosol	
· Colour:	White	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
• Melting point/freezing point:	Undetermined.	
• Boiling point or initial boiling point and boiling		
range	Not applicable, as aerosol.	
· Flammability	Not applicable.	
· Lower and upper explosion limit		
· Lower:	Not determined.	
· Upper:	Not determined.	
· Flash point:	Not applicable, as aerosol.	
· Auto-ignition temperature:	Product is not selfigniting.	
· Decomposition temperature:	Not determined.	
· pH	Not determined.	
· Viscosity:		
· Kinematic viscosity	Not determined.	
· Dynamic:	Not determined.	
· Solubility		
· water:	Fully miscible.	
Partition coefficient n-octanol/water (log value)	Not determined.	
· Vapour pressure:	Not determined.	
		(Con

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

	(Contd. of page
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of heal	th and
environment, and on safety.	
Explosive properties:	Not determined.
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 7,178 mg/kg (rat)

(Contd. on page 6)

GB

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

(Contd. of page 5)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

• 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability The product is biodegradable. Degree of biodegradation> 70%
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- *Recommended cleansing agents: Water, if necessary together with cleansing agents.*

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
· Class · Label	2.1 Gases. 2.1
	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	
EMS Number:	<i>F-D,S-U</i>
Segregation groups	Ammonium compounds
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	<i>litre: Category A. For AEROSOLS with a capacity abo 1 litre: Category B. For WASTE AEROSOLS: Catego</i>
	<i>C, Clear of living quarters. Calego</i>
Segregation Code	SG69 For AEROSOLS with a maximum capacity of
Segreguion coue	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
	<i>ν</i>

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

	(Contd. of page 7)
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Local regulations.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H280 Contains gas under pressure; may explode if heated.
- · Classification according to Regulation (EC) No 1272/2008
- *The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.*

• Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

GB

Printing date 17.03.2022

Version number 3 (replaces version 2)

Revision: 17.03.2022

Trade name: K2 TIRE DOKTOR

(Contd. of page 8)

GB

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

• * Data compared to the previous version altered.

The section that were changed since the last version are marked with an asterisk on the left section number