



Page 1/10

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 1) · Signal word Danger · Hazard-determining components of labelling: reaction mass of ethylbenzene and xylene · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H312+H332 Harmful in contact with skin or if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Keep out of reach of children. P102 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P271 Use only outdoors or in a well-ventilated area. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 Dispose of contents/container to a waste container. • Additional information: Buildup of explosive mixtures possible without sufficient ventilation. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

(Contd. on page 3)

GR

^{· 3.2} Mixtures

[·] Description: Mixture: consisting of the following components.

[·] Dangerous components: EC number: 905-588-0 reaction mass of ethylbenzene and xylene <50% 🚸 Flam. Liq. 3, H226; 🚸 STOT RE 2, H373; Asp. Tox. 1, H304; () Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 CAS: 106-97-8 butane, pure <20% EINECS: 203-448-7 🚯 Flam. Gas 1, H220; Press. Gas (Comp.), H280 CAS: 74-98-6 <15% propane EINECS: 200-827-9 🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280 CAS: 67-63-0 <10% propan-2-ol EINECS: 200-661-7 🐵 Flam. Liq. 2, H225; 🚯 Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119457558-25-XXXX CAS: 112-34-5 <5% 2-(2-butoxyethoxy)ethanol EINECS: 203-961-6 🕩 Eve Irrit. 2, H319 Reg.nr.: 01-2119475104-44-XXXX • Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Personal protection for the First Aider.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 3) Open and handle receptacle with care. · Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use. • 7.2 Conditions for safe storage, including any incompatibilities • Storage: • Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurised containers. · Information about storage in one common storage facility: Not required. • Further information about storage conditions: Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. • 7.3 Specific end use(s) No further relevant information available. **SECTION 8: Exposure controls/personal protection** · 8.1 Control parameters · Ingredients with limit values that require monitoring at the workplace: 106-97-8 butane, pure WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) 67-63-0 propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm 112-34-5 2-(2-butoxyethoxy)ethanol WEL Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm • Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls • Appropriate engineering controls No further data; see item 7. · Individual protection measures, such as personal protective equipment • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

GB

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 4)

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical p	roperties
· General Information	
· Physical state	Aerosol
· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
• Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable, as aerosol.
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Soluble.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
	(Contd. on page 6

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

	(Contd. of page
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of healt	th and
environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of
· · · ·	explosive air/vapour mixtures are possible.
Change in condition	· · · ·
Evaporation rate	Not applicable.
Information with regard to physical hazard c	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised containe
Aerosois	May burst if heated.
Quidicina agas	May burst ij nealea. Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	
Flammable solids	Void Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamme	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Harmful in contact with skin or if inhaled.

(Contd. on page 7)

GB

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

		(Contd.	of pag
		vant for classification:	
ATE (Acu	te Toxicity	Estimates)	
Dermal	LD50	1,254 mg/kg	
Inhalative	LC50/4 h	12.5 mg/l	
reaction m	ass of ethy	vlbenzene and xylene	
Dermal	LD50	1,100 mg/kg (ATE)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
106-97-8 b	utane, pur	re	
Inhalative	LC50/4 h	658 mg/l (rat)	
67-63-0 pr	opan-2-ol		
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (rat)	
112-34-5 2	-(2-butoxy	vethoxy)ethanol	
Oral	LD50	5,660 mg/kg (rat)	
Dermal	LD50	4,000 mg/kg (rabbit)	
Skin corro	sion/irritat	tion Causes skin irritation.	
		irritation Causes serious eye irritation.	
		re May cause respiratory irritation.	
		<i>sure</i> May cause damage to organs through prolonged or repeated exposure. <i>other hazards</i>	
Endocrine	disrupting	g properties	

None of the ingredients is listed.

SECTION 12: Ecological information

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability The product is biodegradable. Degree of biodegradation> 70%
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- **Remark:** Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

(Contd. on page 8)

GB

^{· 12.1} Toxicity

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name ADR IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.	
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat. SW2 Clear of living quarters.	

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

	(Contd. of page
Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
· 14.7 Maritime transport in bulk accordi	ing to IMO
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Local regulations.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

GB

Printing date 13.05.2021

Version number 5 (replaces version 4)

Revision: 13.05.2021

Trade name: K2 EGR, CARB AND THROTTLE CLEANER

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

• * Data compared to the previous version altered.

The section that were changed since the last version are marked with an asterisk on the left section number