



Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: K2 DIESEL GO!
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Diesel injector cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Melle Sp. z o. o.

Stary Staw 9

63-400 OSTRÓW WLKP.

**POLAND** 

· Further information obtainable from:

Product safety department. zakupy@inter-global.com.pl

· 1.4 Emergency telephone number: During normal opening times: 0048/62 737 88 00

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



### health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

(Contd. of page 1)

### · Hazard pictograms









### · Signal word Danger

### · Hazard-determining components of labelling:

reaction mass of ethylbenzene and xylene

2-ethylhexyl nitrate

2-Ethyl-1-hexanol

Hydrocarbons, C10, aromatics, >1% naphthalene

#### · Hazard statements

H226 Flammable liquid and vapour.

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

Causes skin irritation. H315 H319 Causes serious eye irritation. H335 May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. H373

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

Keep out of reach of children. P102 P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to a waste container.

### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

### · 3.2 Mixtures

• **Description:** Mixture: consisting of the following components.

EC number: 905-562-9 reaction mass of ethylbenzene and xylene <	
	< 70%
Reg.nr.: 01-2119555267-33-XXXX  Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
	<10%
EINECS: 248-363-6	
CAS: 104-76-7 2-Ethyl-1-hexanol	<5%
EINECS: 203-234-3	

(Contd. on page 3)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

	(Contd.	of page 2)
EC number: 919-284-0	Hydrocarbons, C10, aromatics, >1% naphthalene	<1%
	♦ Carc. 2, H351; Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	
EC number: 947-523-9	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C16-18(even numbered) and C18 unsaturated acyl) derivs., hydroxides, inner salts  Aquatic Acute 1, H400; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<1%
CAS: 91-20-3	naphthalene	<1%
EINECS: 202-049-5 Reg.nr.: 01-2119561346-37-XXXX	Flam. Liq. 3, H226;  Carc. 2, H351;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Acute Tox. 4, H302	
· Additional information: For the wo	ording of the listed hazard phrases refer to section 16.	

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Personal protection for the First Aider.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

CO2, powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
  - Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/surface or ground water.

(Contd. on page 4)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

104-76-7 2-Ethyl-1-hexanol

WEL Long-term value: 5.4 mg/m³, 1 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

#### · Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid

Light brown
Characteristic
Not determined.

Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined.
• Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.

· Auto-ignition temperature: Product is not selfigniting.

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

water: Soluble.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

(Contd. on page 6)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

		_
Contd. of	nage	5

Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

· Important information on protection of health and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures which emit flammable

Substances and mixtures, which emit flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if swallowed, in contact with skin or if inhaled.

(Contd. on page 7)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

		(Contd. of page 6)
· LD/LC50	values rele	vant for classification:
ATE (Acu	te Toxicity	Estimates)
Oral	LD50	1,923 mg/kg
Dermal	LD50	1,144 mg/kg
Inhalative	LC50/4 h	11.3 mg/l
reaction m	ass of ethy	lbenzene and xylene
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)
27247-96-	7 2-ethylhe	exyl nitrate
Oral	LD50	500 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)
104-76-72	-Ethyl-1-h	exanol
Oral	LD50	2,049 mg/kg (rat)
Dermal	LD50	1,970 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
91-20-3 na	phthalene	
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat)
Chin com		tion Causes skin irritation

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

# SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability The product is biodegradable. Degree of biodegradation> 70%
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

(Contd. of page 7)

Danger to drinking water if even small quantities leak into the ground.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S ENVIRONMENTALLY HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (2-ethylhexyl nitrate, Ethyl-1-hexanol), MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class(es)	
ADR, IMDG	
Class Label	3 Flammable liquids. 3
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substanc 2-ethylhexyl nitrate
Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	30 F-E,S-D

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

	(Contd. of page
Stowage Category	A
· 14.7 Maritime transport in bulk according to IN instruments	MO Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II. ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- 1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

- 2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Local regulations.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

Printing date 03.03.2021 Version number 1 Revision: 03.03.2021

Trade name: K2 DIESEL GO!

(Contd. of page 9)

· Relevant phra	ses
-----------------	-----

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- *H410 Very toxic to aquatic life with long lasting effects.*
- H411 Toxic to aquatic life with long lasting effects.
- EUH044 Risk of explosion if heated under confinement.

EUH066 Repeated exposure may cause skin dryness or cracking.

### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Čategory 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2