


Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31 and 2020/878/EC

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023



Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

(Contd. of page 1)

· Hazard-determining components of labelling:	
Hydrocarbons, C6-C7, n-alkanes, izoalkanes, cyclics, <5% n-hexane	
Hydorcarbons, C9-C11, n-alkanes, isoalkanes, cyclics, $<2\%$ aromatics	
· Hazard statements	
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.	
H315 Causes skin irritation.	
H336 May cause drowsiness or dizziness.	
H411 Toxic to aquatic life with long lasting effects.	
· Precautionary statements	
P102 Keep out of reach of children.	
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No s	smoking.
<i>P211</i> Do not spray on an open flame or other ignition source.	
P251 Do not pierce or burn, even after use.	
P260 Do not breathe spray.	
<i>P271</i> Use only outdoors or in a well-ventilated area.	
P273 Avoid release to the environment.	
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.	
<i>P501</i> Dispose of contents/container to a waste container.	
· 2.3 Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB: Not applicable.	

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture: consisting of the following components.

Dangerous components

CAS: 106-97-8	butane, pure	<50%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
EC number: 921-024-6	<i>Hydrocarbons, C6-C7, n-alkanes, izoalkanes, cyclics, <5% n-hexane</i>	<50%
	 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 	
CAS: 74-98-6	propane	<25%
EINECS: 200-827-9	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
EC number: 919-857-5	<i>Hydorcarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics</i>	<25%
	🚸 Asp. Tox. 1, H304; 🕔 STOT SE 3, H336	
CAS: 75-28-5	isobutane	<10%
EINECS: 200-857-2	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
CAS: 68608-26-4	Sodium sulfonate	<3%
Polymer	♦ Eye Irrit. 2, H319	
EC number: 918-668-5	Hydrocarbons, C9, aromatics	<3%
	 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336 	

(Contd. on page 3)

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Take affected persons out into the fresh air. Personal protection for the First Aider.

• *After inhalation:* Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Not required.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Absorb liquid components with liquid-binding material.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: None.

(Contd. on page 4)

IE

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

(Contd. of page 3)

Trade name: K2 CAVITY WAX

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane, pure

OEL Short-term value: 1000 ppm

74-98-6 propane

OEL Asphx

75-28-5 isobutane

OEL Short-term value: 1000 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• *Eye/face protection* Not required.

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties · General Information · Physical state Aerosol · Colour: Amber coloured · Odour: Characteristic · Odour threshold: Not determined. • *Melting point/freezing point:* Undetermined. · Boiling point or initial boiling point and boiling Not applicable, as aerosol. range · Flammability *Not applicable.* · Lower and upper explosion limit · Lower: Not determined. (Contd. on page 5)

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

	(Contd. of page
Upper:	Not determined.
Flash point:	Not applicable, as aerosol.
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	4
Form:	Aerosol
Important information on protection of health an	a
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	25
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	, 010
gases in contact with water	Void
	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	
Corrosive to metals	Void Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

⁽Contd. on page 6)

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

(Contd. of page 5)

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)OralLD5096,905 mg/kg

 Dermal
 LD50
 111,002 mg/kg

 Inhalative
 LC50/4 h
 611 mg/l (rat)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

Hydorcarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

- Oral LD50 >5,000 mg/kg (rat) (OECD 401)
- Dermal LD50 >5,000 mg/kg (rabbit) (OECD 402)

· Skin corrosion/irritation Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure May cause drowsiness or dizziness.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

• 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 7)

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

(Contd. of page 6)

· 12.7 Other adverse effects

• Additional ecological information:

• General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

- · Recommendation: Disposal must be made according to official regulations.
- *Recommended cleansing agents: Water, if necessary together with cleansing agents.*

SECTION 14: Transport information	ion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class · Label	2 5F Gases. 2.1
· IMDG	
· Class · Label	2.1 Gases. 2.1
·IATA	
· Class · Label	2.1 Gases. 2.1
2	(Contd. on page 8)

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

	(Contd. of page	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR):	Product contains environmentally hazardous substances Hydrocarbons, C6-C7, n-alkanes, izoalkanes, cyclic. <5% n-hexane Symbol (fish and tree) Symbol (fish and tree)	
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abo 1 litre: Category B. For WASTE AEROSOLS: Catego C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class	
14.7 Maritime transport in bulk according to IM instruments		
Transport/Additional information:		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· Transport category · Tunnel restriction code	2 D	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALI HAZARDOUS	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

(Contd. on page 9)

IE

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

(Contd. of page 8)

• Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 \cdot Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Local regulations.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 10)

IE

Printing date 10.01.2023

Version number 3 (replaces version 2)

Revision: 10.01.2023

Trade name: K2 CAVITY WAX

	(Contd. of page 9)
Date of previous version: 27.10.2017	
Version number of previous version: 2	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (Europea	an Agreement Concerning the
International Carriage of Dangerous Goods by Road)	0 0
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
<i>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</i>	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2	